

# AM-480272METMQW-00H AMPIRE 4.3" TFT-LCD screen 480\*272 Display

|                       |                                          |
|-----------------------|------------------------------------------|
| Model                 | AM-480272METMQW-00H                      |
| Brand                 | AMPIRE                                   |
| Category              | <a href="#">AMPIRE</a>                   |
| Resolution            | 480(RGB)×272                             |
| Active Area           | 95.04(W)×53.856(H) mm                    |
| Outline Dim           | 105.5(H)×67.2(V) ×3.1(D) mm              |
| Luminance             | 500 cd/m <sup>2</sup> (Typ.)             |
| View Direction        | 6 o'clock                                |
| Viewing Angle         | 70/70/50/70 (Typ.)(CR?10)                |
| Support Color         | 16.7M 56% NTSC                           |
| Frame Rate            | 60Hz                                     |
| Interface Type        | Parallel RGB (1 ch, 8-bit) , 40 pins FPC |
| Power Supply          | 3.3V (Typ.)                              |
| Operating Temperature | -20 ~ 70 °C                              |
| Panel Type            | a-Si TFT-LCD, LCM                        |
| Pixel Format          | RGB Vertical Stripe                      |
| Bezel Opening         | 99.0(W)×56.86(H) mm                      |
| Treatment             | Antiglare, Hard coating (3H)             |
| Contrast Ratio        | 500:1 (Typ.) (TM)                        |
| Response Time         | 8/17 (Typ.)(Tr/Td)                       |
| Operating Mode        | TN, Normally White, Transmissive         |
| Light Source          | WLED [6S2P] , 25K hours , W/O Driver     |
| Touch Panel           | Without                                  |

**Note:**

Invshop recommends that you inquire with the original factory or its agents about the latest production status and technical information about AM-480272METMQW-00H. The product parameters displayed on Invshop are entered by Invshop engineers according to the specifications, and efforts have been made to minimize errors, but we cannot guarantee the complete correctness of the parameters. Please refer to the specification sheet!

<https://www.invshop.com>

