

DG4V-3-2A-VM-U-H7-60 EATON VICKERS Solenoid Valve Durable Gold Supplier

Model	DG4V-3-2A-VM-U-H7-60
Brand	EATON VICKERS
Model / Part Number	DG4V-3-2A-VM-U-H7-60
Valve Type	Solenoid Operated Directional Control Valve
Interface / Valve Size	ISO 4401-03 (NG6) / NFPA D03
Actuation / Spool Type	Single Solenoid, 2-Position, Spring Offset
Maximum Flow Rate	80 L/min (21 US gpm)
Maximum Pressure	350 bar (5000 psi)
Coil Voltage	24V DC
Electrical Connection	ISO 4400 (DIN 43650) Connector
Seal Material / Fluid Compatibility	"U" (Viton) for Water Glycol / Petroleum Oils
Operating Temperature Range	-20°C to 70°C (-4°F to 158°F)

Note:

Invshop recommends that you inquire with the original factory or its agents about the latest production status and technical information about DG4V-3-2A-VM-U-H7-60. The product parameters displayed on Invshop are entered by Invshop engineers according to the specifications, and efforts have been made to minimize errors, but we cannot guarantee the complete correctness of the parameters. Please refer to the specification sheet!



<https://www.invshop.com>



<https://www.invshop.com>